HP Jet Fusion 3D Printing Solution

Reinventing prototyping and manufacturing



The HP Jet Fusion 3D Printing Solution reinvents how you prototype and produce functional parts, delivering quality output, up to 10 times faster¹ at half the cost²



Superior, consistent part quality

- Get extreme dimensional accuracy and fine detail,³ thanks to HP's unique Multi-Agent printing process
- Produce truly functional parts with optimal mechanical properties,⁴ faster¹
- Obtain predictable, reliable final printed parts that match your design^s
- Access new future materials and uncover new applications thanks to the HP Multi Jet Fusion Open Platform

Breakthrough productivity

- Produce more parts per day with continuous printing and fast cooling¹
- Streamline your workflow with HP's automated materials preparation and post-processing station
- Cleaner experience with an enclosed Processing Station and materials not classified as hazardous⁶
- Rely on HP's world-class Technical Services and Support to maximize uptime and productivity
- Choose your ideal end-to-end solution from a range of printing and processing options

Lowest cost-per-part²

- Achieve lowest cost-per-part² and reduce operational costs, opening your doors to short-run manufacturing
- Benefit from a competitively-priced 3D printing solution²
- Optimize cost and part quality, with costefficient materials that offer industry-leading reusability⁷
- Plan production times more accurately and predictably, to increase your overall operational efficiency

For more information, please visit hp.com/go/3DPrint

HP Jet Fusion 3D 4200/3200 Printing Solution



 1MZ24A
 HP Jet Fusion 3D Printer Yearly Maintenance Kit

 1MZ25A
 HP Jet Fusion 3D Post Processing Maintenance Kit

1MZ23A HP Jet Fusion 3D Printer Initial Maintenance Kit

Automated material mixing and loading systems help streamline your workflow and reduce labor time

No additional room for parts removal needed with **enclosed unpacking and material collection system,** including a laminar hood

> The **HP Jet Fusion 3D Build Unit** included within the printer—is moved on for cooling right after job completion allowing a **continuous printing** process and maximizing productivity¹



Module¹ reduces cooling time resulting in faster¹ time-to-part and more parts ready within the same day



PROCESSING STATION

HP Technical Services and Support

stand behind your business to maximize your uptime and productivity, with next-business-day onsite support⁹ and spare parts availability⁹

	HP Jet	Fusion 3D 3200 Printing Solution
	MOP41A	HP Jet Fusion 3D 3200 Printer
	M0P50A	HP Jet Fusion 3D 3200 Processing Station with Fast Cooling ¹
	M0P45B	HP Jet Fusion 3D Build Unit
	M0P54B	HP Jet Fusion 3D External Tank 5 units Bundle
	M0P54A	HP Jet Fusion 3D External Tank Starter kit
	F9K08A	HP 3D600 Printhead
	V1Q60A	HP 3D600 3L Fusing Agent
	V1Q61A	HP 3D600 3L Detailing Agent
	n/a	n/a
	n/a	n/a
	V1Q66A	HP 3D600 Cleaning Roll
	V1R10A	HP 3D High Reusability PA 12 30L ¹⁰ (13 kg)
usion 3D printers	V1R14A	VESTOSINT [®] 3D Z2773 PA 12 30L ¹⁰ (14 kg), Certified for HP Jet Fusion 3D printers
	U9EJ8E	HP Printer Installation w/Introduction to Basic Operation Service
	U9EL9E	HP Post Processing Installation Service
inting Hrs)	n/a	n/a
rs limit: 7.800)	n/a	n/a
rs limit: 5.800)	U9PK7E	HP 3 year NBD* Onsite Printer Support with DMR** (Printing Hours limit: 5.800)
rs limit: 3.800)	U9PK6E	HP 3 year NBD* Onsite Printer Support with DMR** (Printing Hours limit: 3.800)
rs limit: 1.600)	U9PK5E	HP 3 year NBD* Onsite Printer Support with DMR** (Printing Hours limit: 1.600)
	U9EQ8E	HP 3 year NBD* Onsite Build Unit Support
	U9EM5E	HP 3 year NBD* Onsite Processing Station Support
g Solution	U9EK7E	HP Advanced Operator Training Service for Jet Fusion 3D Printing Solution
	1MZ23A	HP Jet Fusion 3D Printer Initial Maintenance Kit
	1MZ24A	HP Jet Fusion 3D Printer Yearly Maintenance Kit
	1MZ25A	HP Jet Fusion 3D Post Processing Maintenance Kit

* Next Business Day ** Defective Media Retention

Technical specifications¹²

HP Jet Fusion 3D 4200/3200 Printer

Printer	Technology	HP Multi Jet Fusion technology		
performance	Effective building volume	380 x 284 x 380 mm (15 x 11.2 x 15 in) 3200 Printer: 2800 cm ³ /hr (170 in ³ /hr) ¹³ 4200 Printer: 4000 cm ³ /hr (244 in ³ /hr) ¹⁴		
	Building speed			
	Layer thickness	3200 Printer: 0.08 mm (0.003 in) 4200 Printer: 0.07 to 0.1 mm (0.0027 to 0.004 in)		
	Print resolution (x, y)	1200 dpi		
Dimensions (w x d x h)	Printer	2210 x 1200 x 1448 mm (87 x 47 x 57 in)		
	Shipping	2300 x 1325 x 2068 mm (91 x 52 x 81 in)		
	Operating area	3700 x 3700 x 2500 mm (146 x 146 x 99 in)		
Weight	Printer	750 kg (1653 lb)		
	Shipping	945 kg (2083 lb)		
Network ¹⁵	Gigabit Ethernet (10/100/1000Base-T), supporting the following standards: TCP/IP, DHCP (IPv4 only), TLS/SSL			
Hard disk	2 TB (AES-128 encrypted, FIPS 140, disk wipe DoD 5220M)			
Software	Included software	HP SmartStream 3D Build Manager, HP SmartStream 3D Command Center		
	Supported file formats	3mf, stl		
	Certified third-party software	Autodesk® Netfabb® Engine for HP, Materialise Magics with Materialise Build Processor for HP Multi Jet Fusion		
Power	Consumption	9 to 11 kW (typical)		
	Requirements	Input voltage three phase 380-415 V (line-to-line), 30 A max, 50/60 Hz / 200-240 V (line-to-line), 48 A max, 50/60Hz		
Certification	Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (UL listed); EU (LVD and MD com- pliant, EN60950-1, EN12100-1, EN60204-1, and EN1010)		
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)		
	Environmental	REACH		

Service coverage included

Eco Highlights

- Powders or agents and are not classified as hazardous⁶
- Enclosed printing system and automated powder management, including post-processing, for a cleaner and more comfortable environment⁶
- Minimum waste thanks to high reusability of powder⁷
- Take back program for Printheads¹⁷

Find out more about HP sustainable solutions at hp.com/ecosolutions

- Based on internal testing and simulation, HP Jet Fusion 3D average printing time is up to 10x faster than average printing time of comparable FDM & SLS printer solutions from \$100,000 USD to \$300,000 USD on market as of April 2016. Testing variables: Part Quantity-1 full build chamber of parts from HP Jet Fusion 3D at 20% of packing density versus same number of parts on abovementioned competitive devices; Part Size 3D g; Layer thickness: 0.1 mm/0.004 inches.
 Fast Cooling enabled by HP Jet Fusion 3D Processing Station with Fast Cooling, available in July 2017. HP Post Processing Station with Fast Cooling accelerates parts cooling time versus recommended manufacturer time by SLS printer solutions from \$100,000 USD to \$300,000 USD, as tested in April 2016. FDM not applicable. Continuous printing requires an additional HP Jet Fusion 3D Build Unit (standard printer configuration includes one HP Jet Fusion 3D Build Unit).
- 2. Based on internal testing and public data, HP Jet Fusion 3D average printing cost-per-part is half the average cost of comparable FDM & SLS printer solutions from \$100,000 USD to \$300,000 USD on market as of April 2016. Cost analysis based on: standard solution configuration price, supplies price, and maintenance costs recommended by manufacturer. Cost criteria: printing 1 build chamber per day/ 5 days per week over 1 year of 30-gram parts at 10% packing density using HP 3D High Reusability PA 12 material, and the powder reusability ratio recommended by manufacturer.
- Based on dimensional accuracy of ±0.2 mm/0.008 inches, measured after sand blasting with HP 3D High Reusability PA 12 material. See <u>hp.com/go/3Dmaterials</u> for more information on materials specifications.
- Based on the following mechanical properties: Tensile strength at 48 MPa (XYZ), Modulus at 1700-1800 MPa (XYZ). ASTM standard tests with HP 3D High Reusability PA 12 material. See <u>hp.com/</u> go/3Dmaterials for more information on materials specifications.
- Within allowable margin of error. Based on dimensional accuracy of ±0.2 mm/0.008 inches, measured after sand blasting with HP 3D High Reusability PA 12 material. See <u>hp.com/</u> go/3Dmaterials for more information on materials specifications.

HP Jet Fusion 4200/3200 Processing Station with Fast Cooling¹

Features	Automated mixing, sieving, and loading; semi-manual unpacking; fast cooling; external storage tank; compatible with high-capacity material cartridges		
Dimensions (w x d x h)	Processing Station with Fast Cooling ¹	3121 x 1571 x 2400 mm (122.9 x 61.9 x 94.5 in)	
	Shipping	3499 x 1176 x 2180 mm (137.8 x 46.3 x 85.8 in)	
	Operating area	3321 x 3071 x 2500 mm (130.7 x 120.9 x 99 in)	
Weight	Processing Station with Fast Cooling ¹	480 kg (1058 lb)	
	Loaded	810 kg (1786 lb)	
	Shipping	620 kg (1367 lb)	
Power	Consumption	2.6 kW (typical)	
	Requirements	Input voltage single phase 200-240 V (line-to-line), 19 A max, 50/60Hz or 220 -240 V (line-to-neutral), 14 A max, 50Hz	
Certification	Safety	UL 2011, UL508A, NFPA, C22.2 NO. 13-14 compliant; United States and Canada (UL listed); EU (MD compliant, EN 60204-1, EN 12100-1 and EN 1010)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)	
	Environmental	REACH	
Warranty &	One-year Services and Support total coverage ¹⁶		

Service coverage included

For more information, please visit

hp.com/go/3DPrint



- 6. The term "cleaner" does not refer to any indoor air quality requirements and/or consider related air quality regulations or testing that may be applicable. The HP powder and agents do not meet the criteria for classification as hazardous according to Regulation (EC) 1272/2008 as amended.
- 7. HP Jet Fusion 3D print solution with HP 3D High Reusability PA 12 has the highest post-production surplus powder reusability with 80% reusability vs any other powder based 3DP technology using PA 12 material. Consistent performance with only 20% powder refresh rate.
- 8. For advanced data features charges may apply in the future
- 9. Available in most countries, subject to Terms & Conditions of HP Limited Warranty and/or Service Agreement. Please consult your local sales representatives for further details.
- 10. 30L refers to the materials container size and not the actual materials volume.
- 11. Only available until September 2017.
- 12. For latest technical specifications, please visit hp.com/go/3Dprint
- 13. Based on 0.08-mm (0.003-in) layer thickness and 10.9 sec/layer.
- 14. Based on 0.1-mm (0.004-in) layer thickness and 9 sec/layer
- 15. The HP Jet Fusion 3D Printing Solution should be connected to the HP Cloud in order to guarantee the correct functioning of the printer and to offer better support.
- 16.Three months Standard Limited Warranty plus thereafter, special intro offer of nine months of support at no additional charge. Only available in certain countries and subject to Terms and Conditions of HP Limited Warranty and/or Service Agreement. Please consult with your local sales representatives for further details.
- 17. Printing supplies eligible for recycling vary by printer. Visit <u>hp.com/recycle</u> to see how to participate and for HP Planet Partners program availability; program may not be available in your area. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.



© Copyright 2016-2017 HP Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.