



Portable Monitor with USB Type-C™



Portable Monitor		
	Size	15.6 inch (DPM2405-1561), 14 inch (DPM2405-1411)
	Panel	CSOT
LCD Panel	Display size	15.6", 14" ELED
	Brightness(Typical)	250cd/m ² (Typ)
	NTSC	45%
	Contrast(Typical)	1200:1 (Typ)
	Active Area(mm)	344.16 (H)×193.59 (V)
	Pixel Pitch(um)	179.25(H)×179.25(V)
	Resolution (H x V)	1920 (H) ×1080 (V)
	Aspect Ratio	16:9
	Response Time(Typical)	20ms (Typ)
	View Angles LR,UD(CR>10)	H 178°/ V 178°(Min)
	Panel Surface	Anti-Glare
	Display Colors	16.7M(6bit+FRC)
PC Input Range	Vertical Freq.	58 to 62Hz
	Max. display frequency (Resolution H*V/Fv)	1920 ×1080 /60Hz
Interface	Input 1	TYPE-C (Full-featured USB-C) × 2
	Input 2	HDMI x 1
Output Terminal	Earphone	Earphone x 1
	Speaker(Typic)	1W*2(8Ω)
Projection screen	Wireless projection	NA
	Wired projection	NA
Power	Consumption(Typical)	On: ≤10W Standby≤0.5W, Off≤0.5W
	PD POWER	DC: 5V-4A/9V-2A/12V-1.5A
	Power Mode	Power on : GREEN (LED)
	Indicator Light	Power saving : RED (LED)
Operating Condition	Temperature	0°C ~ 40°C
	Humidity	20% ~ 85%, non-condensing
Physical	Dimension (W*D*H)	356.26x224.47x10.9mm
	Net Weight	1200g
	Tilt	90°
	VESA Mounting	YES(75mm)
Controls	Front Control	Menu, Bri (-), Vol(+) Auto/Enter, Power (Key)
	On Screen Display	Standard OSD format
	Color	9300,6500, User Mode
	Preset Mode	Standard
Accessory	Type-c Cable	*1
	Mini HDMI-HDMI Cable	*1
	User Manual(Paper)	*1

